

TECHNICALS FEATURES

MATERIAL

INSULATOR : Special PPS (Polyphenylene Sulfide Fibreglass filled thermoplastic) UL 94-V0

- Radiation resistance
- No humidity absorption
- Oxygen free

Note : PPS characteristics are recognized for space applications

SIGNAL CONTACTS for PCB:

- Male :**
- Contact area Copper alloy / Ni + Au 1µ
 - Contact tail Copper alloy / Ni + Au flash 0.1µ

FIXING HARDWARE :

- Jackscrew : Stainless steel

ELECTRICAL for LF Contacts

- All contacts 3 A max. @ 25°C
2.2 A max. @ 85°C
- Working voltage (sea level) Tested at 800 V DC
- Proof voltage Tested at 1200 V DC
- Contact resistance (initially) max. 10 mΩ
- Insulation resistance 1000 MΩ min

MECHANICAL for LF Contacts

- Mechanical operations 500 cycles min. up to 2500.
- Contact insertion and withdrawal force 2 N max. / 0.2 N min. per contact


ENVIRONMENTAL

- Temperature range From -60°C to +260°C
- Vibration severity 0.75mm, 10 g RMS 6 hours long random with superimposed sinusoid. No intermittencies measured when using an H.S.L.I. (High Speed Logic Interrupt) detector with a trip threshold of 2 ns.
- Shock severity 100g for 6 ms
- Solvent resistance HcFc 141 BMGX (ATOCHEM) solvent
- Salt spray test 96 hrs
- Humidity test 56 days @ 90% humidity



CONNECTOR SERIES 320 MALE									
LF contact number nnn	Distance between the axes in mm		Length in mm	LF contacts reference mark number					
	A	B		D	E	F	G	H	J
006	2	11	17	1	2	3	4	5	6
009	4	13	19	1	3	4	6	7	9
012	6	15	21	1	4	5	8	9	12
015	8	17	23	1	5	6	10	11	15
018	10	19	25	1	6	7	12	13	18
021	12	21	27	1	7	8	14	15	21
024	14	23	29	1	8	9	16	17	24
027	16	25	31	1	9	10	18	19	27
030	18	27	33	1	10	11	20	21	30
033	20	29	35	1	11	12	22	23	33
036	22	31	37	1	12	13	24	25	36
039	24	33	39	1	13	14	26	27	39
042	26	35	41	1	14	15	28	29	42
045	28	37	43	1	15	16	30	31	45
048	30	39	45	1	16	17	32	33	48
051	32	41	47	1	17	18	34	35	51
054	34	43	49	1	18	19	36	37	54
057	36	45	51	1	19	20	38	39	57
060	38	47	53	1	20	21	40	41	60
063	40	49	55	1	21	22	42	43	63
066	42	51	57	1	22	23	44	45	66
069	44	53	59	1	23	24	46	47	69
072	46	55	61	1	24	25	48	49	72
075	48	57	63	1	25	26	50	51	75
078	50	59	65	1	26	27	52	53	78
081	52	61	67	1	27	28	54	55	81
084	54	63	69	1	28	29	56	57	84
087	56	65	71	1	29	30	58	59	87
090	58	67	73	1	30	31	60	61	90
093	60	69	75	1	31	32	62	63	93
096	62	71	77	1	32	33	64	65	96
099	64	73	79	1	33	34	66	67	99
102	66	75	81	1	34	35	68	69	102
105	68	77	83	1	35	36	70	71	105
108	70	79	85	1	36	37	72	73	108
111	72	81	87	1	37	38	74	75	111
114	74	83	89	1	38	39	76	77	114
117	76	85	91	1	39	40	78	79	117
120	78	87	93	1	40	41	80	81	120

3D view scale : 1.5 : 1



Marking referee page 12-13 of CMM catalogue

 www.nicomatic.com Mail : nicomatic@nicomatic.fr Tel : +33 (0)4.50.36.13.85	2	26/01/09	H.L.	E.M.	D.Z.
	Iss	Date	Drawn	Checked	Approved
Item : Connector CMM320 male straight on PCB, nnn pts, H01					
Folder : X:\Méthodes\Plans clients\Plans clients 20\24 - CMM320\Connecteur Mâles\321YL\321YLnnnH01_cl					

This document and drawings, sketches, and schematic drawings are the property of the NICOMATIC company, and no parts thereof may be reproduced and used without the written consent of the owner. Law dated 11.03.1902

Catalogue Reference : **321YLnnnH01**

	General tolerance ±0.2	Scale 2:1	Page 1/1
--	------------------------	-----------	----------